# Resurrection Series The Rebirth of a Classic



24 gauge





 $\mathcal{G}_{ ext{ntroducing}}$  the Apache and Rawhide Series. A distinctive design in steel sectional garage doors. The exterior of the door is embossed with a woodgrain texture nish accented by a vintage raised panel design. The Apache and Rawhide are quality constructed 2-inch thick uninsulated steel sectional garage doors o ering exceptional value without sacri cing beauty or durability.

Specifications: Sections are 2-inches thick and manufactured from hot-dipped galvanized steel. Sections are pre-painted embossed with a woodgrain texture, RITS™ reinforced integral truss system AND optional window designs. Tongue and groove-meeting rails are roll formed into the panel. Vertical stile members are 19 gauge hot-dipped galvanized I-beams. Galvanized stiles are riveted and bonded to the interior face of the door with an siliconbased cement. Bottom sections are reinforced with aluminum "L" angle and bonded to the section for supporting a replaceable UV protected bottom weather seal. Insulation optional.

Exclusive RITS™ "Reinforced Integral Truss System" design for increased section strength that include tongue and groove weather resistant meeting rails. Optional CFC free Polystyrene insulation with a rigid vinyl back skin, R factor of 6.25. Laminated PVC backing is available as a factory installed option.



- 24 gauge • 26 gauge
- Short panel only
- 21" high sections
- Galvanized stiles
- Shadow groove
- White only
- H1 or H2
- Hardware pack



- Short panel only
- 18" & 21" high sections
- Galvanized stiles
- No shadow groove
- White, almond, sandstone & brown
- H2 or H3 Hardware pack



\* Availabile for Rawhide Series only. Check with your local Dealer for price and availability.



### **Reinforced Aluminum Bottom Extrusion**

Heavy duty grooved "U" type weather seal is set into an aluminum reinforced "L" angle, and bonded to the bottom section.



**I-Beam Center Stiles** 

Galvanized I-beam center stiles are engineered to reinforce the construction of the section and designed to eliminate the use of plastic reinforcement angles when the section is post insulated.









EXTREME TEMPERATURES
















## WARRANTY

First United Door Technologies warrants each garage door and component parts to be free from defects in material and workmanship to the original purchaser. A copy of this warranty is available upon request.









### Distributed By:

# 1st United Door Technologies, LLC

7255 S. Kyrene Road • Tempe, Arizona 85283 Phone: 480-705-6632 • Fax: 480-705-8497 Toll Free: 866-366-7636 • sales@firstudt.com www.firstudt.com